

Peerless Chain Co.

1416 E. Sanborn St.,
Winona MN 55987

Phone: 507-457-9100 • **Fax:** 800-356-1149

Email: custserv@peerlesschain.com • **Website:** www.peerlesschain.com

Item # 6800026, Trailer Chains

Trailer Chains



Class 1 - All types of trailers with a trailer Gross Vehicle Weight Rating (GVWR) (trailer pounds including its load) not to exceed 2,000 lbs (910 kg). Two chains must be used per trailer.

Class 2 - All types of trailers with a GVWR of over 2,000 lbs (910 kg) and not to exceed 3,500 lbs (1,590 kg) GVWR.

Class 3 - All types of trailers with a GVWR of over 3,500 lbs (1,590 kg) and not to exceed 5,000 lbs (2,270 kg) GVWR. Two chains must be used per trailer.

Class 4 & Above - All types of trailers with a GVWR of over 5,000 lbs (2,270 kg) and not to exceed 10,000 lbs (4,540 kg) GVWR. Two chains must be used per trailer.

[SPECIFICATIONS](#) · [NOTE](#) · [WARNING](#)

SPECIFICATIONS

Material	Low Carbon Steel
Finish	Yellow Zinc
Ends	36" with Clevis Slip Hook & Latch on One End
Unit of Order	Piece
Gross Vehicle Weight Rating (GVWR)	Not to exceed 26,400 lbs (11,970 kg)
Class	N/A
Minimum Breaking Strength	26400 lbs
Trade Size (Inches)	3/8 G70
Length	36 in
Hooks	1 Clevis Slip Hook & Latch
Qty. Per Drum	100
Lbs. Per Drum	185
GVWR - Lbs.	26400
GVWR - Kgs.	11975

NOTE

Other sizes and configurations available upon request.

WARNING

See Trailer Safety Chain Guidelines

Do not exceed Working Load Limits (WLL)!

See the "Cautions and Warnings" section before using these products.
